

Office: 086 110 6381
Fax: 086 514 8109
mail@instantflooring.co.za



INSTANT
FLOORING
IT'S A KIND OF MAGIC!!!

Spectrum Deck U : PRODUCT SPECIFICATIONS

Module Size: Width: 609.6 mm

Length: 304.8 mm

Thickness: 28.58 mm

Module Weight: 1306 grams

Per Square Meter: 7.03 kg.

Material:

High-impact polypropylene co-polymer. UV Inhibitors added.

Fire Rating:

UL 94HB (Underwriters Laboratory Yellow Card Number)

This test signifies that this product does not flare up when exposed to an open flame and has a slow burn rate of 2" per minute for a 2" wide, 0.5 millimeter thickness test sample.

ASTM 2859 (Flammability of Finished Texture Floor Covering Materials)

– passed test

* Testing reports available for fire ratings

Hot Wire Ignition Rating: 3

Melting Point: 162 ° C

Support Structure:

Flooring module incorporates multi-directional structural support ribbing, allowing for distribution of weight and loads.

Weight Loading:

20,000 lbs sq/ft static load, solid sub-surface. Varies depending on subsurface.

Ground Surfaces:

UltraDeck is designed to be used with little ground preparation over grass, gravel, sand, soil, concrete, asphalt, ice, snow, mud, synthetic turf, rubberized tracks, and other standard surfaces.

Functional Features:

a) Individual modules interconnect to form larger flooring sections.

Office: 086 110 6381
Fax: 086 514 8109
mail@instantflooring.co.za



INSTANT
FLOORING
IT'S A KIND OF MAGIC!!!

- b) Connection system allows for installation and disassembly *without* the need for connection or separation tools.
- c) Modules feature integrated, multi-directional cable channels on the underside of each tread, for running power and communication wiring or rope lighting.
- d) Modules are designed to allow 90-degree rotation and still connect. Module can be connected in both directions and at any module connection point, allowing greater flexibility in floor design.
- e) Modules do not have any submerged channels into which debris or dirt can enter from the top surface, and are easy to clean and maintain.

Warranty: 3 Year warranty against manufacturer's defects.